

RVV 铜芯聚氯乙烯软电线电缆

CCC RVV Copper core PVC sheathed cable

阻燃Antiflaming ROHS REACH



1. 产品应用 APPLICATION:

本产品主要用于中/小型家用电器，仪表仪器，电源传输等用途，也可以传输控制信号和动力信号，并适合敷设在管道或桥架里面。

This product is mainly used for medium / small household appliances, instruments, power transmission and other purposes. It can also transmit control signals and power signals, and is suitable for laying in pipes or bridges.

2. 产品说明 PRODUCT DESCRIPTION:

技术参数 technical parameter

型号 TYPE : 52 (RVV) / 53 (RVV)

结构描述 structure

标准 standards :

GB/T 5023.5-2008/IEC 60227-5:2003

导体: 多根裸软细铜丝绞合, 符合GB/T3956第5类导体规定
conductor Barewire conform to GB/T3956 and IEC 60228

电压 Rated Voltage :

300/300V:52 (RVV) 300/500V:53 (RVV)

绝缘: 阻燃环保型PVC绝缘 (PVC/D型), 线芯采用颜色识别。
insulation PVC insulation, Color distinction.

温度 Use Temperature :

弯曲bend: -0°C 至 +70°C 静态still : -10°C 至 +70°C

成缆: 绝缘线芯采用最佳绞合节距成缆
cabling The wire core is twisted with the best pitch

最小弯曲半径 Bend Radius 

弯曲bend: 12×外径0.D

静态still : 8×外径0.D

外护套: 阻燃环保型 PVC 护套 (PVC/ST5型)
sheath PVC, conform to GB/T 5023.1

型号TYPE	规格specification 芯数×截面mm ²	外径OD 约mm	认证资质 authentication	型号TYPE	规格specification 芯数×截面mm ²	外径OD 约mm	认证资质 authentication
60227 IEC 52 (RVV) 300/300V	2 × 0.5	5.5	CCC	60227 IEC 53 (RVV) 300/500V	2 × 1.0	7.0	CCC
	2 × 0.75	6.1	CCC		2 × 1.5	8.0	CCC
	3 × 0.5	5.9	CCC		3 × 1.0	7.5	CCC
	3 × 0.75	6.6	CCC		3 × 1.5	8.8	CCC

备注: 以上产品护套颜色默认为黑色, 如需其它颜色请在订单上面注明。

* 其它规格请咨询我司技术人员 TEL: